

Grease PumpsMake your machines smoother, faster





Ideal lubrication solutions

Benefits of ATS- ELGI make Grease pumps:

- Dispensing of grease at optimum pressure
- High performance pumps that last longer
- Longer life for high quality delivery hoses
- Very convenient to use and portable

Hand operated grease pump



Technical Specifications

H	GH 00 004 : Grease	<u>o</u>	Output per Stroke: 3 g		
	Single Cylinder, Portable & Static, Drum type with cover	0	Blocked Pressure: 140 Kg/cm²		
Hose Type	Wire braided, Oil resistant, High pressure Hose	0	Delivery Hose Length: 2.2 mts		
The state of the s	ID of Hose : 6 mm		Drum Capacity: 5/10/20 Kg		

Air operated grease pump



Technical Specifications

中美	Grease Pump: GP 50 001		Air requirement (FAD) : 425 lpm
<u>⋄</u>	Pressure Ratio: 50:1		Grease grade: NLGI 00,0,1,2
<u>o</u>	Output at 8.5 Kg/cm²: 300 - 400 g	Hose Type	Wire braided, Oil resistant, High pressure Hose
(Max Working Pressure: 10.5 Kg/cm ²	0	Delivery Hose Length: 1.1 / 2.2 mts
0	Recomm.Working Pressure: 4.5 to 8.5 Kg/cm ²	Man .	ID of Hose: 6 mm
O	Grease Blocked Pressure@ 8.5 Kgf/cm² Air pressure: 425 Kgf/cm²		Drum Capacity: 25/50/200 Litres

Application:

- Body Greasing and Hub Greasing of Light/Heavy Commercial Vehicles
- Tightening of Traction Chain in Earth Moving Equipments
- Lubricating the Machinery in Industries
- Other greasing requirements in Automobile/Industry segments



ATS ELGI Ltd.,

(A wholly owned subsidiary of Elgi Equipments Ltd.,)

Private Industrial Estate, Kurichy, Coimbatore - 641021, India. Tel: +91-422-2589999 | Email: enquiry@ats-elgi.com

Visit us at : www.ats-elgi.com

Toll-free number: 1800-425-3544

Working Hrs: Monday - Saturday: 9:00AM - 7:00PM